

(*) The values shown represent the minimum value of the vehicle in the basic configuration, and the maximum value that includes the maximum weight of accessories available and that can be installed in the basic configuration in the factory.

S= standard O=optional - = not available VTR: Fiberglass

Kronos				
low-profile				
295 TL				
298 TL				
CHASSIS	WEIGHT KG			
Mechanical unit	-	Ford Transit	Fiat Ducato	Ford Transit
Engine, Power hp	-	2.0 TdI 130 CV	2.3 MJ 120 CV	2.0 TdI 130 CV
Maximum technically permissible weight (Kg)	-	3900	3900	3900
Weight unladen in running conditions (Kg)*	-	2925 / 3077	2888 / 3077	3005 / 3072
Payload**	-	423 / 575	423 / 612	428 / 495
Wheelbase (mm)	-	3750	3800	3954
Wheels dimensions	-	16"	15"	16"
Manual air conditioning	-	S	S	S
Driver and Passenger airbag	-	S	S	S
Cruise Control with speed limiter	-	S	S	S
ABS / ESC / Traction+	-	S / S / -	S / S / 0	S / S / -
Swivelling driver' and passenger's seat / Cab seat covers	-	S / S	S / S	S / S
Radio bluetooth 2 DIN FIAT / FORD	3	- / S	- / 0	- / S
DIMENSIONS AND PLACES				
External length (mm) / External width (mm)	-	6990 / 2350	6980 / 2350	7430 / 2350
External height(mm) / Internal height (mm)	-	2950 / 2080	2950 / 2080	2950 / 2080
Homologated seats	-	5	5	5
Berths	-	4 (5 0)	4 (5 0)	4 (5 0)
Berths (optional dinette)	1	0	0	0
Rear Bed (mm)	-	2160x1350(1200)	2070x1290	2070x1290
Bed in Dinette (mm)	-	2160x900(500)	2160x890	2160x890
Overcab bed (mm)	-	-	-	-
Elevating Bed (mm)	-	1900x1280(1070)	1900x1330(1240)	1900x1330(1240)
Additional seat rear bed	-	-	-	-
Locker (useful opening, mm)	-	1300x1020(720)	1300x1020(720)	1300x1020(720)
Max. internal garage height (mm)	-	1300	1300	1300
Floor / walls / roof thickness (mm)	-	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31
Floor / walls / roof material (mm)	-	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR
Fiberglass roof, hail-proof	-	S	S	S
INSTALLATIONS				
Burners / Gas oven / Suction hood	-/14-15/-	3 / 0 / -	3 / 0 / -	3 / 0 / -
Tank capacity clear water / wastewater (L)	-	(20) 100 / 120	(20) 100 / 120	(20) 100 / 120
Automatic trivalent fridge (220V, 12V, gas) (L)	-	140	140	140
Compressor refrigerator (L)	-	-	-	-
Standard heating system	0 / 1	Combined Gas 4KW	Combined Gas 4KW	Combined Gas 4KW
Space for 2 gas bottles (tot. Max 15 Kg)	-	S	S	S
Bathroom window (double opaque glass)	-	S	S	S
Shower tray with double drain	-	S	S	S
Integrated and isolated entry step	-	S	S	S
Heated garage locker	-	S	S	S
SKYLIGHT				
Panoramic roof - OPEN SKY (mm)	-	S (100x800)	S (100x800)	S (100x800)
Rear skylight (mm)	6	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)
Central skylight (mm)	6	400x400	400x400	400x400
Dinette skylight (mm)	-	-	-	-
Double-glazed windows with blind / mosquito net	-	S / S	S / S	S / S
EQUIPMENTS				
Pleated cab blind	6	-	-	-
Flex Space (rear bed height adjustment)	25	S	S	S
Beds with slats	-	S	S	S
Internal LED lightening	-	S	S	S
EXTERIORS				
Rear camera	-	S	S	S
Solar panel	-	S	S	S
Entrance door with fixed window / Flyscreen for entrance door	-	S / S	S / S	S / S
Entrance door with two central locking points	-	S	S	S
Storage space on sideskirt (exterior part)	11	-	-	-
Painted front bumper	-	S	S	S

overcab				
277 M				
279 M				
284 M				
290 M				
295 M				
CHASSIS	WEIGHT KG			
Mechanical unit	-	Ford Transit	Fiat Ducato	Ford Transit
Engine, Power hp	-	2.0 TdI 130 CV	2.3 MJ 120 CV	2.0 TdI 130 CV
Maximum technically permissible weight (Kg)	-	3900	3900	3900
Weight unladen in running conditions (Kg)*	-	2890 / 2907	2978 / 3157	2935 / 2992
Payload**	-	593 / 610	343 / 522	508 / 565
Wheelbase (mm)	-	3954	4035	3750
Wheels dimensions	-	16"	15"	16"
Manual air conditioning	-	S	S	S
Driver and Passenger airbag	-	S	S	S
Cruise Control with speed limiter	-	S	S	S
ABS / ESC / Traction+	-	S / S / -	S / S / 0	S / S / -
Swivelling driver' and passenger's seat / Cab seat covers	-	S / S	S / S	S / S
Radio bluetooth 2 DIN FIAT / FORD	-	- / S	- / 0	- / S
DIMENSIONS AND PLACES				
External length (mm) / External width (mm)	-	6990 / 2350	7450 / 2350	7330 / 2350
External height(mm) / Internal height (mm)	-	3200 / 2080	3200 / 2080	3200 / 2080
Homologated seats	-	7	6	6
Berths	-	7	8	4 (5 0)
Berths (optional dinette)	-	0	0	0
Rear Bed (mm)	-	2120x800 - 2120x800	2160x1300(1120) - 2100x1100	1970x800-2220(2060)x800
Bed in Dinette (mm)	-	1860x1250	1860x1250	2160x1160(540)
Overcab bed (mm)	-	2090x1600	2090x1600	2090x1600
Elevating Bed (mm)	-	-	-	-
Additional seat rear bed	-	-	-	-
Locker (useful opening, mm)	-	1070x600	1300x1020(720)	1170x870(720)
Max. internal garage height (mm)	-	1300	1300	1300
Floor / walls / roof thickness (mm)	-	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31
Floor / walls / roof material (mm)	-	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR
Fiberglass roof, hail-proof	-	S	S	S
INSTALLATIONS				
Burners / Gas oven / Suction hood	-	3 / 0 / -	3 / 0 / -	3 / 0 / -
Tank capacity clear water / wastewater (L)	-	(20) 100 / 120	(20) 100 / 120	20 (100) / 120
Automatic trivalent fridge (220V, 12V, gas) (L)	-	140	140	140
Compressor refrigerator (L)	-	-	-	-
Standard heating system	-	Combined Gas 4KW	Combined Gas 4KW	Combined Gas 4KW
Space for 2 gas bottles (tot. Max 15 Kg)	-	S	S	S
Bathroom window (double opaque glass)	-	S	S	S
Shower tray with double drain	-	S	S	S
Integrated and isolated entry step	-	S	S	S
Heated garage locker	-	S	S	S
SKYLIGHT				
Panoramic roof - OPEN SKY (mm)	-	0 (800x600)	0 (800x600)	0 (800x600)
Rear skylight (mm)	6	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)
Central skylight (mm)	6	400x400	400x400	400x400
Dinette skylight (mm)	-	-	-	-
Double-glazed windows with blind / mosquito net	-	S / S	S / S	S / S
EQUIPMENTS				
Pleated cab blind	6	-	-	-
Flex Space (rear bed height adjustment)	25	S	S	S
Beds with slats	-	S	S	S
Internal LED lightening	-	S	S	S
EXTERIORS				
Rear camera	-	S	S	S
Solar panel	-	S	S	S
Entrance door with fixed window / Flyscreen for entrance door	-	S / S	S / S	S / S
Entrance door with two central locking points	-	S	S	S
Storage space on sideskirt (exterior part)	-	-	-	-
Painted front bumper	-	S	S	S

motorhome				
265 INTEGRAL				
267 INTEGRAL				
274 INTEGRAL				
284 INTEGRAL				
287 INTEGRAL				
295 INTEGRAL				
CHASSIS	WEIGHT KG			
Mechanical unit	-	Ford Transit	Fiat Ducato	Ford Transit
Engine, Power hp	-	2.0 TdI 130 CV	2.3 MJ 120 CV	2.0 TdI 130 CV
Maximum technically permissible weight (Kg)	-	3900	3900	3900
Weight unladen in running conditions (Kg)*	-	2978 / 3157	2968 / 3072	2923 / 2988
Payload**	-	343 / 522	428 / 532	512 / 577
Wheelbase (mm)	-	4035	4035	4035
Wheels dimensions	-	15"	15"	15"
Manual air conditioning	-	S	S	S
Driver and Passenger airbag	-	S	S	S
Cruise Control with speed limiter	-	S	S	S
ABS / ESC / Traction+	-	S / S / 0	S / S / 0	S / S / 0
Swivelling driver' and passenger's seat / Cab seat covers	-	S / S	S / S	S / S
Radio bluetooth 2 DIN FIAT / FORD	-	- / 0	- / 0	- / 0
DIMENSIONS AND PLACES				
External length (mm) / External width (mm)	-	7450 / 2350	7450 / 2350	7450 / 2350
External height(mm) / Internal height (mm)	-	2950 / 2080	2950 / 2080	2950 / 2080
Homologated seats	-	5	6	5
Berths	-	4 (5 OPT)	6	4 (5 OPT)
Berths (optional dinette)	-	0	0	0
Rear Bed (mm)	-	1900x1500	2160x1000(840) - 2160x1000(840)	2200x800 - 1940x800
Bed in Dinette (mm)	-	2120x540	2000x620 - 1890x650	2120x540
Overcab bed (mm)	-	-	-	-
Elevating Bed (mm)	-	1900x1350	1900x1350	1900x1350
Additional seat rear bed	-	-	-	-
Locker (useful opening, mm)	-	1170x870(720)	1000x670	1170x870(720)
Max. internal garage height (mm)	-	1280	1190	1200
Floor / walls / roof thickness (mm)	-	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31
Floor / walls / roof material (mm)	-	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR
Fiberglass roof, hail-proof	-	S	S	S
INSTALLATIONS				
Burners / Gas oven / Suction hood	-	3 / 0 / -	3 / 0 / -	3 / 0 / -
Tank capacity clear water / wastewater (L)	-	20 (100) / 100	20 (100) / 100	20 (100) / 100
Automatic trivalent fridge (220V, 12V, gas) (L)	-	140	140	140
Compressor refrigerator (L)	-	-	-	-
Standard heating system	-	Combined Gas 4KW	Combined Gas 4KW	Combined Gas 4KW
Space for 2 gas bottles (tot. Max 15 Kg)	-	S	S	S
Bathroom window (double opaque glass)	-	S	S	S
Shower tray with double drain	-	S	S	S
Integrated and isolated entry step	-	S	S	S
Heated garage locker	-	S	S	S
SKYLIGHT				
Panoramic roof - OPEN SKY (mm)	-	-	-	-
Rear skylight (mm)	6	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)
Central skylight (mm)	6	400x400	400x400	400x400
Dinette skylight (mm)	-	-	-	-
Double-glazed windows with blind / mosquito net	-	S / S	S / S	S / S
EQUIPMENTS				
Pleated cab blind	6	-	-	-
Flex Space (rear bed height adjustment)	25	S	S	S
Beds with slats	-	S	S	S
Internal LED lightening	-	S	S	S
EXTERIORS				
Rear camera	-	S	S	S
Solar panel	-	S	S	S
Entrance door with fixed window / Flyscreen for entrance door	-	S / S	S / S	S / S
Entrance door with two central locking points	-	S	S	S
Storage space on sideskirt (exterior part)	-	-	-	-
Painted front bumper	-	S	S	S

(*) The values shown represent the minimum value of the vehicle in the basic configuration, and the maximum value that includes the maximum weight of accessories available and that can be installed in the basic configuration in the factory.

S= standard 0=optional - = not available VTR: Fiberglass

(*) The values shown represent the minimum value of the vehicle in the basic configuration, and the maximum value that includes the maximum weight of accessories available and that can be installed in the basic configuration in the factory.

S= standard O=optional - = not available VTR: Fiberglass

low-profile							
		Zefiro		295 TL		298 TL	
CHASSIS		WEIGHT KG					
Mechanical unit	-	-	Ford Transit	Fiat Ducato	Ford Transit	Fiat Ducato	
Engine, Power hp	-	-	2.0 TdI 130 CV	2.3 MJ 120 CV	2.0 TdI 130 CV	2.3 MJ 120 CV	
Maximum technically permissible weight (Kg)	-	-	3500	3500	3500	3500	
Weight unladen in running conditions (Kg)*	-	-	2925 / 3077	2888 / 3077	3005 / 3072	3005 / 3072	
Payload	-	-	423 / 575	423 / 612	428 / 485	428 / 485	
Wheelbase (mm)	-	-	3750	3800	3954	3954	
Wheels dimensions	-	-	16"	15"	16"	15"	
Manual air conditioning	-	-	S	S	S	S	
Driver and Passenger airbag	-	-	S	S	S	S	
Cruise Control with speed limiter	-	-	S	S	S	S	
ABS / ESC / Traction	-	-	S / S / -	S / S / 0	S / S / -	S / S / 0	
Swivelling driver' and passenger's seat / Cab seat covers	-	-	S / S	S / S	S / S	S / S	
Radio bluetooth 2 DIN FIAT / FORD	3	-	- / S	- / 0	- / S	- / 0	
DIMENSIONS AND PLACES							
External length (mm) / External width (mm)	-	-	6990 / 2350	6990 / 2350	7430 / 2350	7430 / 2350	
External height(mm) / Internal height (mm)	-	-	2950 / 2080	2950 / 2080	2950 / 2080	2950 / 2080	
Homologated seats	-	-	5	5 (OPT)	5	5 (OPT)	
Berths	-	-	4	5 (OPT)	4	5 (OPT)	
Berths (optional dinette)	1	-	-	-	-	-	
Rear Bed (mm)	-	-	2160x1350(1200)	2070x1290	2160x1350	2070x1290	
Bed in Dinette (mm)	-	-	2160x900(500)	2160x890	2160x900	2160x890	
Overcab bed (mm)	-	-	-	-	-	-	
Elevating Bed (mm)	-	-	1900x1280(1070)	1900x1330(1240)	1900x1280(1070)	1900x1330(1240)	
Additional seat rear bed	-	-	-	-	-	-	
Locker (useful opening, mm)	-	-	1300x1020(720)	1300x1020(720)	1300x1020(720)	1300x1020(720)	
Max. internal garage height (mm)	-	-	1300	1300	1300	1300	
Floor / walls / roof thickness (mm)	-	-	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	54 / 31 / 31	
Floor / walls / roof material (mm)	-	-	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	VTR / VTR / VTR	
Fiberglass roof, hail-proof	-	-	S	S	S	S	
INSTALLATIONS							
Burners / Gas oven / Suction hood	-/14-15/-	-	3 / 0 / -	3 / 0 / -	3 / 0 / -	3 / 0 / -	
Tank capacity: clear water / wastewater (L)	-	-	20 (100) / 100	20 (100) / 100	20 (100) / 100	20 (100) / 100	
Automatic trivalent fridge (220V, 12V, gas) (L)	-	-	140	140	140	140	
Compressor refrigerator (L)	-	-	-	-	-	-	
Standard heating system	0 / 1	-	Combined Gas 4KW	Combined Gas 4KW	Combined Gas 4KW	Combined Gas 4KW	
Space for 2 gas bottles (tot. Max 15 Kg)	-	-	S	S	S	S	
Bathroom window (double opaque glass)	-	-	S	S	S	S	
Shower tray with double drain	-	-	S	S	S	S	
Integrated and isolated entry step	-	-	S	S	S	S	
Heated garage locker	-	-	S	S	S	S	
SKYLIGHT							
Panoramic roof - OPEN SKY (mm)	-	-	S (100x800)	S (100x800)	S (100x800)	S (100x800)	
Rear skylight (mm)	6	-	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	400x400 (0 700x500)	
Central skylight (mm)	6	-	400x400	400x400	400x400	400x400	
Dinette skylight (mm)	-	-	-	-	-	-	
Double-glazed windows with blind / mosquito net	-	-	S / S	S / S	S / S	S / S	
EQUIPMENTS							
Pleated cab blind	6	0	-	-	-	-	
Flex Space (rear bed height adjustment)	25	S	S	S	S	S	
Beds with slats	-	-	S	S	S	S	
Internal LED lightening	-	-	S	S	S	S	
EXTERIORS							
Rear camera	-	-	S	S	S	S	
Solar panel	-	-	S	S	S	S	
Entrance door with fixed window / Flyscreen for entrance door	-	-	S / S	S / S	S / S	S / S	
Entrance door with two central locking points	-	-	S	S	S	S	
Storage space on sideskirt (exterior part)	11	S	S	S	S	S	
Painted front bumper	-	-	S	S	S	S	

overcab					277 M					279 M					284 M					290 M					295 M														
Ford Transit		Fiat Ducato		Ford Transit		Fiat Ducato		Ford Transit		Fiat Ducato		Ford Transit		Fiat Ducato		Ford Transit		Fiat Ducato		Ford Transit		Fiat Ducato																	
2.0 TdI 130 CV		2.3 MJ 120 CV		2.0 TdI 130 CV		2.3 MJ 120 CV		2.0 TdI 130 CV		2.3 MJ 120 CV		2.0 TdI 130 CV		2.3 MJ 120 CV		2.0 TdI 130 CV		2.3 MJ 120 CV		2.0 TdI 130 CV		2.3 MJ 120 CV																	
3500		3500		3500		3500		3500		3500		3500		3500		3500		3500		3500		3500																	
2890 / 2907		2878 / 2907		2935 / 2992		2990 / 3072		3025 / 3072		3008 / 2992		3015 / 3072		3008 / 3072		3015 / 3072		3008 / 3072		2935 / 2992		2935 / 2992																	
593 / 610		593 / 622		508 / 565		428 / 502		428 / 478		508 / 592		428 / 485		428 / 482		508 / 565		508 / 565		508 / 565		508 / 565																	
3954		4035		3750		4035		3954		3800		3954		4035		3750		3954		3750		3750																	
16"		15"		16"		15"		16"		15"		16"		15"		16"		16"		16"		15"																	
S		S		S		S		S		S		S		S		S		S		S		S																	
S		S		S		S		S		S		S		S		S		S		S		S																	
S / S / -		S / S / 0		S / S / -		S / S / 0		S / S / -		S / S / 0		S / S / -		S / S / 0		S / S / -		S / S / 0		S / S / -		S / S / 0																	
S / S		S / S		S / S		S / S		S / S		S / S		S / S		S / S		S / S		S / S		S / S		S / S																	
- / S		- / 0		- / S		- / 0		- / S		- / 0		- / S		- / 0		- / S		- / 0		- / S		- / 0																	
6990 / 2350					7450 / 2350					6990 / 2350					7330 / 2350					7450 / 2350					7450 / 2350					6990 / 2350					6970 / 2350				
3200 / 2080					3200 / 2080					3200 / 2080					3200 / 2080					3200 / 2080					3200 / 2080					3200 / 2080									
7					6					5					4 (5 OPT)					4 (5 OPT)					6					6									
2120x800 - 2120x800					2160x1300(1120) - 2100x1100					1970x800-2220(2060)x800					2120x1890					2150x1280(1110)					1860x1250					2090x1600									
1860x1250 - 1600x650					2090x1600					2100x1160(540)					2120x1300(500)					2090x1600					2090x1600					2090x1600									
1070x600					1300x1020(720)					1170x870(720)					1320x1370					1300x1020(720)					1300x1020(720)														
1070x600					1300x1020(720)					1170x870(720)					1320x1370					1300x1020(720)					1300x1020(720)														
1200					1380					1190					1430					1300					1300														
54 / 31 / 31					54 / 31 / 31					54 / 31 / 31					54 / 31 / 31					54 / 31 / 31					54 / 31 / 31														
VTR / VTR / VTR					VTR / VTR / VTR					VTR / VTR / VTR					VTR / VTR / VTR					VTR / VTR / VTR					VTR / VTR / VTR														
S					S					S					S					S					S														
3 / 0 / -					3 / 0 / -					3 / 0 / -					3 / 0 / -					3 / 0 / -					3 / 0 / -														
20 (100) / 100					110 (20) / 100					20 (100) / 100					20 (100) / 100					20 (100) / 100					20 (100) / 100														
140					140					140					140					140					140														
Combined Gas 4KW					Combined Gas 4KW					Combined Gas 4KW					Combined Gas 4KW					Combined Gas 4KW					Combined Gas 4KW														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
0(800x600)					0(800x600)					0(800x600)					0(800x600)					0(800x600)					0(800x600)														
400x400 (0 700x500)					400x400 (0 700x500)					400x400 (0 700x500)					400x400 (0 700x500)					400x400 (0 700x500)					400x400 (0 700x500)														
400x400					400x400					400x400					400x400					400x400					400x400														
S / S					S / S					S / S					S / S					S / S					S / S														
0					0					0					0					0					0														
-					-					-					-					-					-														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														
S					S					S					S					S					S														

makohome											
265 INTEGRAL		267 INTEGRAL		274 INTEGRAL		284 INTEGRAL		287 INTEGRAL		295 INTEGRAL	
Fiat Ducato 2.3 MJ 120 CV 3500 2978 / 3157 343 / 522 4035 15" S S S S / S / 0 S / S		Fiat Ducato 2.3 MJ 120 CV 3500 2968 / 3072 428 / 532 4035 15" S S S S / S / 0 S / S		Fiat Ducato 2.3 MJ 120 CV 3500 2923 / 2988 512 / 577 4035 15" S S S S / S / 0 S / S		Fiat Ducato 2.3 MJ 120 CV 3500 2978 / 3157 343 / 522 4035 15" S S S S / S / 0 S / S		Fiat Ducato 2.3 MJ 120 CV 3500 2968 / 3072 428 / 532 4035 15" S S S S / S / 0 S / S		Fiat Ducato 2.3 MJ 120 CV 3500 2878 / 3077 423 / 522 3800 15" S S S S / S / 0 S / S	
- / 0 - / 0 - / 0		7450 / 2350 2950 / 2080 5 4 4 (5 OPT) 0 1900x1500 2120x540 -		7300 / 2350 2950 / 2080 5 4 4 0 2160x1000(840) - 2160x1000(840) 2000x620 - 1890x650 -		7450 / 2350 2950 / 2080 5 4 4 (5 OPT) 0 2200x800 - 1940x800 2120x540 -		7450 / 2350 2950 / 2080 5 4 4 0 2000x800 - 2150x800 2120x540 -		6970 / 2350 2950 / 2080 5 4 4 (5 OPT) 0 2160x1350(1200) 2160x900(800) -	
-		1900x1350		1900x1350		1900x1350		1900x1350		1900x1350	
1170x870(720) - 720x870(720)		1170x870(720) - 720x870(720)		1000x670 - 1000x670		1170x870(720) - 1170x870(720) 1170x870(720) - 1170x870(720)		1170x870(720) - 1170x870(720)		1300x1020(720) - 1300x1020(720)	
1280 54 / 31 / 31 VTR / VTR / VTR S		1280 54 / 31 / 31 VTR / VTR / VTR S		1380 54 / 31 / 31 VTR / VTR / VTR S		1190 54 / 31 / 31 VTR / VTR / VTR S		1200 54 / 31 / 31 VTR / VTR / VTR S		1300 54 / 31 / 31 VTR / VTR / VTR S	
3 / 0 / - 20 (100) / 100 140		3 / 0 / - 20 (100) / 100 140		3 / 0 / - 20 (100) / 100 140		3 / 0 / - 20 (100) / 100 140		3 / 0 / - 20 (100) / 100 140		3 / 0 / - 20 (100) / 100 140	
Combined Gas 4KW		Combined Gas 4KW		Combined Gas 4KW		Combined Gas 4KW		Combined Gas 4KW		Combined Gas 4KW	
S S S S S S		S S S S S S		S S S S S S		S S S S S S		S S S S S S		S S S S S S	
-		-		-		-		-		-	
400x400 (0 700x500) 700x500 (0 HEK 3 960x555)		400x400 (0 700x500) 700x500 (0 HEK 3 960x555)		400x400 (0 700x500) 700x500 (0 HEK 3 960x555)		400x400 (0 700x500) 700x500 (OPT HEK 3 960x555)		400x400 (0 700x500) 700x500 (0 HEK 3 960x555)		400x400 (0 700x500) 700x500 (OPT HEK 3 960x555)	
S / S		S / S		S / S		S / S		S / S		S / S	
-		-		-		-		-		-	
S		S		S		S		S		S	
-		-		-		-		-		-	
S		S		S		S		S		S	
-		-		-		-		-		-	
S		S		S		S		S		S	
S / S		S / S		S / S		S / S		S / S		S / S	
S		S		S		S		S		S	
S		S		S		S		S		S	
S		S		S		S		S		S	
S		S		S		S		S		S	

(*) The values shown represent the minimum value of the vehicle in the basic configuration, and the maximum value that includes the maximum weight of accessories available and that can be installed in the basic configuration in the factory.

S= standard O=optional - = not available VTR: Fiberglass

	low-profile		
	Granduca	267 TL	287 TL
CHASSIS			
WEIGHT (kg)			
Mechanical unit	-	Fiat Ducato	Fiat Ducato
Engine, Power hp	-	2.3 MJ / 120 CV	2.3 MJ / 120 CV
Maximum technically permissible weight (Kg)	-	3500	3500
Weight unladen in running conditions (Kg)	-	3103 / 3157	3103 / 3157
Payload*	-	343 / 397	343 / 397
Wheelbase (mm)	-	4035	4035
Wheels dimensions	-	15"	15"
Manual air conditioning	-	S	S
Driver and Passenger airbag	-	S	S
Cruise Control with speed limiter	-	S	S
Swivelling driver* and passenger's seat / Cab seat covers	-	S / S	S / S
Painted front bumper	-	S	S
DIMENSIONS AND PLACES			
External length (mm) / External width (mm)	-	7450 / 2350	7450 / 2350
External height(mm) / Internal height (mm)	-	3050 / 2080	3050 / 2080
Homologated seats	-	4	4
Berths	-	4	4
Rear Bed (mm)	-	1900x1500	2000x800
Elevating Bed (mm)	-	1900x1280(1070)	1900x1300(1240)
Additional seat rear bed	-	-	S
Locker (useful opening, mm)	-	1170x870(720)	1170x870(720)
Max. internal garage height (mm)	-	1220	1190
Floor / walls / roof thickness (mm)	-	38-22 / 31 / 31	38-22 / 31 / 31
Floor / walls / roof material (mm)	-	VTR / VTR / VTR	VTR / VTR / VTR
Fiberglass roof, half-proof	-	S	S
INSTALLATIONS			
Burners / Gas oven / Suction hood	- / 14-15 / -	3 / 0 / -	3 / 0 / -
Tank capacity: clear water / wastewater (L)	-	(20) 80 / 80	(20) 80 / 80
Automatic trivalent fridge (220V, 12V, gas) (L)	-	150	150
Standard heating system	0 / 1	Combined Gas 4KW	Combined Gas 4KW
Space for 2 gas bottles (tot. Max 15 Kg)	-	S	S
Bathroom window (double opaque glass)	-	S	S
Shower tray with double drain	-	S	S
Integrated and isolated entry step	-	S	S
Heated garage locker	-	S	S
Technical double floor	-	S	S
SKYLIGHT			
Panoramic roof - OPEN SKY (mm)	-	S (1000x800)	S (1000x800)
Rear skylight (mm)	6	400x400 (Ø 700x500)	400x400 (Ø 700x500)
Central skylight (mm)	6	400x400	400x400
Double-glazed windows with blind / mosquito net	-	S	S
EQUIPMENTS			
Cab	-	S / 0	S / 0
Beds with staves	-	S	S
Internal LED lightening	-	S	S
EXTERIOR			
Rear camera	-	S	S
Solar panel	-	S	S
Entrance door with fixed window	-	S	S
Flyscreen for entrance door	-	S	S
Entrance door with two central locking points	-	S	S
External LED light	-	S	S

	Van	Livingstone K2	Livingstone 2	Livingstone 4	Livingstone 5	Livingstone 6	Livingstone DUO
CHASSIS							
WEIGHT (kg)							
Mechanical unit	-	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato	Fiat Ducato
Engine, Power hp	-	2.3 MJ / 90(120) CV	2.3 MJ / 90(120) CV	2.3 MJ / 130(180) CV	2.3 MJ / 90(120) CV	2.3 MJ / 90(120) CV	2.3 MJ / 90(120) CV
Maximum technically permissible weight (Kg)	-	3300	3300	3300	3300	3300	3300
Weight unladen in running conditions (Kg)	-	2663 / 2773	2753 / 2853	2803 / 2903	2773 / 2873	2833 / 2883	2903 / 2983
Payload	-	395	345	545	345	345	335
Wheelbase (mm)	-	3450	4035	4035	4035	4035	4035
Maximum towable weight (kg)	-	2500	2500	2500	2500	2500	2500
Wheels dimensions	-	15"	15"	15"	15"	15"	15"
Driver and Passenger airbag	-	S / 0	S / 0	S / 0	S / 0	S / 0	S / 0
ABS / ESC / Traction+	-	S / S / 0	S / S / 0	S / S / 0	S / S / 0	S / S / 0	S / S / 0
Swivelling driver* and passenger's seat / Cab seat covers	- / 3	S / 0	S / 0	S / 0	S / 0	S / 0	S / 0
Painted cab / Metallic colour	-	WHITE/O	WHITE/O	WHITE/O	WHITE/O	WHITE/O	WHITE/O
DIMENSIONS AND PLACES							
External length (mm) / External width (mm)	-	5410 / 2050	6365 / 2050	5995 / 2050	5995 / 2050	5995 / 2050	5995 / 2050
External height(mm) / Internal height (mm)	-	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890	2650 / 1890
Homologated seats	-	4	4	4	4	4	4
Berths	-	2	2+1	2+1	4+1	2+1	2+1
Rear Bed (mm)	-	1900x1330	1900x1440	1900x1440	1860x1440 - 1860x1320	1740x750 - 1900x620	1950x800 - 1900x800
Bed in Dinette (mm)	-	1400x450	1800x970	1800x970	1800x970	1750x900	1500x500
Beds with staves	-	S	S	S	S	S	S
INSTALLATIONS							
Burners	-	2	2	2	2	2	2
Tank capacity: clear water / wastewater (L)	-	90/90	100/90	100/90	100/90	100/90	100/90
trivalent fridge (220V, 12V, gas) (L)	-	-	80	140	80	-	80
Compressor fridge (L)	-	85	-	-	85	-	-
Standard heating system	-	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL	4000Kw DIESEL
Space for 2 gas bottles (tot. Max 7 Kg)	-	S	S	S	S	S	S
Bathroom window (double opaque glass)	-	S	S	S	S	S	S
Shower tray with double drain	-	S	-	S	-	-	-
Internal insulation material	-	ECOFIBER	ECOFIBER	ECOFIBER	ECOFIBER	ECOFIBER	ECOFIBER
Floor thickness (mm)	-	30	30	30	30	30	30
SKYLIGHT							
400x400 skylight (mm) with blind / mosquito net	-	2	2	2	2	2	2
700x600 skylight (mm) with blind / mosquito net	-	S	S	S	S	S	S
EQUIPMENTS							
Cab	-	S / 0	S / 0	S / 0	S / 0	S / 0	S / 0
Table extension in dinette	-	S	S	S	S	S	S

notes

The masses indicated in this catalogue refer to the provisions of European Directive 2007/46/EC.

MASS IN RUNNING ORDER
It includes the weight of the empty base vehicle, of the driver (75 kg), 100% of the fuel (60+ tank), fresh water (tank filled with 20 l while travelling), and a gas tank for living purposes (20 kg). The mass in running order, and consequently the payload and/or certified seats may vary depending on the accessories installed.

PAYLOAD
This consists of the difference between the maximum technically permissible laden mass and the mass in running order. It includes elements for living purposes, the transported passengers defined by the manufacturer (driver excluded), and the personal effects.
The payload calculation is based on the following parameters: 75 kg for each passenger (driver excluded), 10 kg of baggage for each passenger and for the driver, 10 kg for each metre of length of the vehicle, plus the remaining payload, which can be used for the installation of accessories or for additional baggage. All masses and loads of the empty vehicle have a tolerance of +/- 5%, in compliance with Directive 2007/46/EC. Any optional equipment increases the mass in running order and decreases the payload. The weight of non-standard accessories is not included in the mass in running order indicated in this catalogue. Additional accessories and devices reduce the payload by a quantity equal to their weight; the incidence of the weight of the individual accessories is shown in the special column in the technical data sheets or can be requested at our dealers. In case certain accessories are installed (for example, additional elements such as coupling device or motorbike rack), the mass of these accessories will affect the payload, possibly reducing it along with the number of certified seats. Please make sure that the maximum loads on the axes and the maximum technically permissible load mass are not exceeded during the complete loading phase of the vehicle. The regulations and requirements of each country may entail changes in the characteristics of this table.

The number of certified seats may vary depending on the traffic regulations in force in each country.



(*) The values shown represent the minimum value of the vehicle in the basic configuration, and the maximum value that includes the maximum weight of accessories available and that can be installed in the basic configuration in the factory.

S = standard 0 = optional - = not available VTR: Fiberglass